

ROCKIES
4910 N Moline St Denver, CO 80239
720-923-5023

GREAT PLAINS
16820 W 113th Street Lenexa, KS 66219
913-522-6598



www.rusoh.com
1.800.318.2944

RUSOH^{INC.}

SEE WHAT
WE CAN
DO FOR YOU



Introducing the Industry's First Fire Extinguisher Designed to be Maintained and Recharged by the Owner.

Owner Maintained reduces costs by eliminating the 6-year internal exam and third-party service requirements.*

Universal Design is easy for a left or right-handed person to operate, saving time when seconds count.

CO₂ Cartridge-Based design is more reliable and safer than stored pressure extinguishers.

Engineered Polymer construction is corrosion-proof, resists impacts, and is 100% recyclable for sustainability.

High Efficiency valve and nozzle assembly improve agent discharge, knocking down flames faster and giving the user more protection.

Recharge Kit (sold separately) has everything you need to recharge your Rusoh® Eliminator® fire extinguisher in minutes and put it back into service.



*Some states may require additional maintenance/licensing. Contact your sales representative and/or local fire official for more information.

RUSOH INC. EXTINGUISHER SPECIFICATIONS

Agent Type	2.5 lb ABC Dry Chemical	5 lb ABC* Dry Chemical	10 lb ABC* Dry Chemical	10 lb ABC* High-Flow Dry Chemical
Stock:	09306	09300	09308	09314
UL & ULC Rating:	1A:10B:C	3A:40B:C	4A:80B:C	1A:20B:C
Capacity:	2.5 lb (1.1 kg) nom	5 lb (2.3 kg) nom	10 lb (4.5 kg) nom	10 lb (4.5 kg) nom
Agent:	MAP**	MAP**	MAP**	MAP**
Weight:	5.95 lbs (2.7 kg)	12.1 lbs (5.5 kg)	19.5 lb (8.8 kg)	19.5 lb (8.8 kg)
Height:	14.68 in (37.29 cm)	16.75 in (42.54 cm)	21.5 in (54.6 cm)	21.5 in (54.6 cm)
Width:	7.13 in (18.11 cm)	8.5 in (21.59 cm)	10.4 in (26.4 cm)	10.4 in (26.4 cm)
Depth:	5.05 in (12.83 cm)	5.7 in (14.47 cm)	6.2 in (15.8 cm)	6.2 in (15.8 cm)
Discharge Range:	6-8 ft (1.8-2.4 m)	12-18 ft (4-6 m)	15-21 ft (4.6-6.4 m)	15-25 ft (4.6-7.6 m)
Discharge Time:	> 8 secs	>13 secs	>21 secs	>9 secs
ANSI/UL 299 & 711:	Yes	Yes	Yes	Yes
USCG Approval†:	Type BC - Size I	Type A-Size II Type BC-Size II	Type A-Size II Type BC-Size II	Type A-Size II Type BC-Size II
Warranty:	6 years	8 Years	8 Years	8 Years

*Also available in PK (Potassium Bicarbonate) models

** High Performance Monoammonium Phosphate

Meets or exceeds ANSI/UL 299 and ANSI/UL 711; USCG-approved with proper bracket; UL listed

Revised 11/15/22